

Network Cabinets

DESCRIPTION

Our Sframe™ Network Cabinets are engineered for quick assembly and immediate use in your data center operations, with specifications designed to accommodate installation of any standard rack-mounted networking equipment

FEATURES

- tempered glass doors for visibility and security
- equipped with casters and support feet
- cooling fans for improved ventilation
- easy replacement of doors and side panels
- rotary locks on all cabinet doors



SPECIFICATIONS

- 19-inch mounting width suitable for most networking equipment
- Conforms to industry standard ANSI/EIA-310-D and IEC 60297-3 mounting configuration
- 800kg (1760lbs) static load capacity
- Body and frame fabricated from cold rolled steel
- Matte black powder-coated finish (also available in white)

DOOR OPTIONS

Sframe™ Network Cabinets are offered with an option of three types of door options:



smokey-gray glass door (default)



perforation steel door (optional)



steel casement door (optional)

Sframe™ images, data, and content © 2015, 2016 Davis Legend. All rights reserved.



CABINET CONFIGURATIONS

NO.	ITEM	QTY	UNIT	MATERIAL	SURFACE FINISH	REMARKS
1	Top cover	1	PC	1.2mm cold-rolled steel	Powder coating	----
2	Frame	2	PC	1.2mm cold-rolled steel	Powder coating	----
3	Front door	1	PC	1.2mm blue-gray transparent tempered glass	----	----
4	Side panel	2	PC	1.2mm cold-rolled steel	Powder coating	With lock latch
5	Rear door	1	PC	1.2mm cold-rolled steel	Powder coating	
6	Lock	2	PC	----	----	----
7	Mounting rail	4	PC	2.0mm cold-rolled steel	Powder coating	----
8	Mounting angle	6	PC	1.5mm cold-rolled steel	Powder coating	
9	Bottom plate	1	PC	1.2mm cold-rolled steel	Powder coating	5 removable cable passing pedestal included
10	Fixed shelf	2	PC	1.2mm cold-rolled steel	Powder coating	1 pc for 27/18U
11	Caster (Front)	2	PC	----	----	
12	Caster (Rear)	2	PC	----	----	With brake lock function
13	Supporting foot	4	PC	----	----	----
14	Cooling fan	4	PC	----	----	2 pcs for 600mm depth cabinet
15	M6 Screw and nut	40	set	----	----	20 sets for 18U/27U
16	M5 Screw	40	set	----	----	20 sets for 18U/27U

CONFIGURATIONS

Network Cabinets are offered in the following standard configurations

RACK UNITS	CABINET HEIGHT	CABINET WIDTH	CABINET DEPTH	PART NUMBER	DOOR	COLOR
18U	988mm (38.90 inches)	600mm (23.62 inches)	600mm(23.62 inches)	SCB-PKST-02-18U66	D(perforation steel door) A(steel casement door) B(smokey-gray glass door)	CBK(black) CWH(white)
27U	1388mm (54.65 inches)		600mm(23.62 inches)	SCB-PKST-02-27U66		
37U	1833mm (72.16 inches)		800mm(31.50 inches)	SCB-PKST-02-27U68		
			800mm(31.50 inches)	SCB-PKST-02-37U68		
42U	2055mm (80.91 inches)		600mm(23.62 inches)	SCB-PKST-02-42U66		
			800mm(31.50 inches)	SCB-PKST-02-42U68		
			1000mm(39.37 inches)	SCB-PKST-02-42U610		
47U	2278mm (89.69 inches)		600mm(23.62 inches)	SCB-PKST-02-47U66		
			800mm(31.50 inches)	SCB-PKST-02-47U68		
			1000mm(39.37 inches)	SCB-PKST-02-47U610		

- Standard configurations can be ordered as <PART NUMBER>-<COLOR> (eg. SCB-PKST-02-42U610-BA-CBK)
- Custom configurations also available upon request, please contact our Sales team for more information

