

# 24 Way Patch Panel CAT6A

## DESCRIPTION

Sharkrack™ patch panels offer high performance and reliability. Designed to be easily installed to meet the requirements of all CAT6A networking by incorporating removable CAT6A Keystone Jacks for a fast termination and more customised solution.







## SPECIFICATIONS

- Cat6A 24-port unshielded patch panels exceed Cat6A 550 MHz connecting hardware requirements; comply with 10 Gigabit Ethernet application system, suit for interaction and termination of horizontal cabling between devices equipment and centralized points.
- The Cat6A 24-port patch panels have unique exterior design, simple and compact.
- The unique designed PCB reduces EMI/RFI interference, with low attenuation loss and high return loss.
- High strength die-casted zinc alloy shielded design meets the industry standards.
- Meet the requirements of both T568A and T568B, with colour labels.
- 110 krone puch downt compatibe. 4 pair one crimp tool available for fast teminations.
- Solid and anticorrosive phosphor bronze IDC guarantees 250 terminations.
- Accept 23-26 AWG wires; phosphor bronze contact with 50μ" gold plating, with a durability of 1500 matching recycles.
- All ports are clearly labeled, suitable for 19" equipment racks, cabinets and wall mount shelf.
- Backward compatible with Cat6 or lower level.

## LOSS AND RESISTANCE

| Description | Parameter |
|---|---|
| Contact resistance(max) | 100mΩ |
| Insulation resistance(min) | 500mΩ |
| Return loss(dB) | 5.9dB |

## DIMENSIONS









## CONFIGURATIONS

| PART NUMBER | DESCRIPTION | HEIGHT | WIDTH | DEPTH |
|---|---|---|---|---|
| DPPC6AU24 | SharkRack 24 Port Patch Panel Cat6A UTP Fully Loaded | 43.8mm (1.72 inches) | 482mm (19 inches) | 90.8mm (3.57 inches) |

V2024.1

SHARKRACK™ images, data, and content © 2015, 2016 Davis Legend. All rights reserved.